

# A-VR / A-VRF SERIES

Diffusers




## DESCRIPTION

- Diffuser can be used for both air intake and exhaust.
- Recommended for ceiling and drop ceiling applications.
- 360 degree diffusion pattern.
- The baffle can be rotated to obtain the required air consumption listed in the specifications.
- Contains no flange (A-VR). Easy installation using the retaining ring.
- Diffusers are manufactured of UL94 certified plastic.

## DIMENSIONS

Model	Measurements [in.]								Air pass, Sq.Ft	Damper normal pitch, inch
	Ø D	Ø D1	Ø D2	Ø D3	H max	H1	H2			
<b>A 100 VRF</b>	3 15/16"	3 5/16"	3 9/16"	5 13/16"	2 9/16"	1 3/4"	1"		0.0648	0..13/16"
<b>A 125 VRF</b>	4 15/16"	4 1/8"	4 5/16"	6 9/16"	2 3/4"	1 9/16"	1 3/16"		0.0861	0..7/8"
<b>A 150 VRF</b>	5 7/8"	4 15/16"	5 1/16"	7 7/8"	3 1/8"	1 15/16"	1 3/16"		0.0968	0..7/8"
<b>A 200 VRF</b>	7 7/8"	6 15/16"	5 1/16"	9 11/16"	3 1/8"	2 1/16"	1 5/16"		0.0861	0..3/4"



Model	Measurements [in.]							Air pass, Sq.Ft	Damper normal pitch, inch
	Ø D	Ø D1	Ø D2	H	H1	H max			
<b>A 100 VRF</b>	3 15/16"	3 9/16"	5 13/16"	2 5/16"	1 1/8"	1 9/16"		0.0648	0..13/16"
<b>A 125 VRF</b>	4 15/16"	4 5/16"	6 9/16"	2 5/16"	1 3/16"	1 15/16"		0.0861	0..7/8"
<b>A 150 VRF</b>	5 7/8"	5 1/16"	7 7/8"	2 5/16"	1 3/16"	1 15/16"		0.0968	0..7/8"
<b>A 200 VRF</b>	7 7/8"	5 1/16"	9 11/16"	2 5/16"	1 3/16"	1 7/8"		0.0861	0..3/4"
<b>A 200/150 VRF</b>	5 7/8"	5 1/16"	9 11/16"	3 1/4"	1 3/16"	1 7/8"		0.0861	0..3/4"

