

PRODUCT SPECIFICATIONS





DESCRIPTION

Specifically designed for direct air exhaust through the wall the VENTS OVK1 series fans are perfect ventilation solutions for parking garages, agricultural facilities and stores. These fans can effectively and quietly handle major ventilation challenges such as large warehouses without taking up valuable space.

CASING

The fans' body is made of steel with polymeric coating while the impeller is made of aluminum.

MOTOR


Asynchronous motor on ball bearings and thermal protection ensure safe and smooth operation.

SUITABLE FOR:

Commercial, educational, government or industrial buildings.

DIMENSIONS

M-J-1	Measurements [in.]						
Model	ØD	Ø D1	Ø D2	Ød	L		
OVK1 200	8 3/16"	10 5/8"	11 13/16"	1/4"	4 3/4"		
OVK1 250	10 5/16"	13"	14 3/16"	1/4"	5 ^{1/2} "		
OVK1 315	12 5/16"	15 3/8"	16 9/16"	3/8"	6 11/16"		











PERFORMANCE

_	ia ia si		*8	CFM vs. Static Pressure (Ps) in WG				Ø	<u> 7</u>		
Model	R PP *	Sones	Duct Dia	Мах Wal	Max Watts* Max Amps*	0"	0.125"	0.25"	0.375"	Max.Ps	Volts/Hz
0VK1 200	1680	2.5	8 3/16"	43	0.63	262	211	56	-	0.30	115
0VK1 250	1640	41	10 5/16"	84	1.17	475	428	288	113	0.45	115
0VK1 315	1430	5.1	12 5/16"	109	1.37	766	626	-	-	0.15	115

MODEL	QUANTITY	COMMENTS	PROJECT
			location:
			architect:
			engineer:
			contractor:
			submitted by:

Tel: 888-640-0925 Fax: 513-583-5786 Sales@Vents-us.com Vents-US.com 400 Murray Rd, Cincinnati, OH 45217



